

R410A

A +A
Energy Class



HPR18RL14AA

HPR24RL14AA

Capacity rated	Cooling	Frig / h	4540	6264
		W	5280	7284
	Heating	BTU/h	18005	24838
		kCal / h	4660	7315
Humidity extraction rate	L / h	W	5420	8506
		BTU/h	18482	29005
Working temperature range		°C	-	-
Power input rated	Cooling	W	1640	2269
	Heating	W	1503	2356
EER		W/W	3,22	3,21
Energy efficiency class			A	A
Annual energy consumption		kWh	820	1134,5
COP		W/W	3,61	3,61
Heating performance class			A	A
Power supply		V - Hz	230-50	230-50
		Phases	1	1
Max power input	Cooling	W	2130	2713
	Heating	W	2080	2695
Current input rated	Cooling	A	7,35	10,38
	Heating	A	6,74	10,78
Starting current		A	40	61
Sound Pressure Level	Indoor	dB(A)	38/40/42	44/46/49
	Outdoor	dB(A)	58	58
I.U. air capacity (max speed)		m ³ /h	780	1005
Indoor units dimensions	width	mm	898	1033
	height	mm	280	313
	depth	mm	202	202
Outdoor units dimensions	width	mm	820	902
	height	mm	605	650
	depth	mm	300	307
Weight	Indoor	kg	11	14
	Outdoor	kg	40	56
Refrigerant	Type		R410A	R410A
	Charge	kg	1,15	1,9
Pipe diameter	Suction	in	1/2	5/8
	Delivery	in	1/4	3/8
Max refrigerating pipe length		m	15	15
Max stand. charge pipe length		m	4,5	5
Supplementary charge pipe		g/m	30	30
Maximum difference in level		m	5	5
Compressor	Type		Rotary	Rotary