

RCL12RL CASSETTE TYPE

RCL12R



CASSETTE LINE		RCL12RL
Cooling output	Frig/h	2975
Cooling output	W	3460
Cooling output	BTU	11798
Heating output	Kcal/h	3199
Heating output	W	3720
Heating output	BTU	12685
Humidity extraction rate	L/h	1,3
Cooling electric power	W	1118
Heating electric power	W	1088
EER		3,09
Energy efficiency class		B
Annual energy consumption	kWh	559
COP		3,41
Heating performance class		B
Power supply	V - Hz	230 – 50
N° of phases		1
Max power input cooling	W	1276
Max power input heating	W	1275
Rated cooling current	A	5,12
Rated heating current	A	4,98
Noise level I.U. max	dB(A)	43
Noise level O.U. max	dB(A)	56
I.U. air capacity (max speed)	m³/h	610
Indoor unit dimensions (WxHxD)	mm	570x310x570
Front panel dimensions (WxHxD)	mm	720X40X720
Outdoor unit dimensions (WxHxD)	mm	760X552X256
Indoor unit weight	Kg	24
Outdoor unit weight	Kg	34
Type of refrigerant		R410a
Refrigerant charge	Kg	0,94
Suction pipe diameter	in	1/2
Delivery pipe diameter	in	1/4
Drainage pipe	mm	10
Max refrigerating pipe length	m	10
Max standard charge pipe length	m	3,5
Supplementary charge pipe	g/m	20
Maximum difference in level	m	5
Type of rotary compressor		SANYO



RCLO12RL



Remote controller